



L, mm	W, mm	H, mm
1216	176	147
1496	176	

D1, mm	D2, mm	weight, kg
1092	96	4.6
1372		5.6

FREELINE is a slim profile suspended luminaire suitable for a wide range of commercial interiors. Equipped as standard with a low glare micro-prismatic diffuser UGR<19. Freeline provides a direct / indirect distribution (LG3) for a soft uniform balanced environment.

Product Code	Description	Weight
FRELED30	1216x176mm 30W 4872 lumen direct / indirect UGR<19 4000K	4.6kg
FRELED44	1216x176mm 44W 7309 lumen direct / indirect UGR<19 4000K	4.6kg
FRELED38	1496x176mm 38W 6273 lumen direct / indirect UGR<19 4000K	5.6kg
FRELED57	1496x176mm 57W 9408 lumen direct / indirect UGR<19 4000K	5.6kg
/ E3	Integral 3hr emergency	
/ DD	DALI control	
/ SL	Silver finish	

Options

- Blank infill section for continuous runs
- Through wiring solutions
- Surface mounted versions
- 3000K
- Tunable white via bluetooth
- Other lumen packages available upon request
- RAL colour to special order

Features

- Slim minimal profile
- UGR<19 micro-prismatic diffuser
- Direct / indirect distribution (LG3)
- 100,000hr L80B50